Nobuyuki Miyazaki, Kawasaki, Japan Shun-ichi Kota, Kawasaki, Japan Takashi Taka, hagi, Kawasaki, Japan Bunji Uchino, Kawasaki, Japan INVENTOR:

ASSIGNEE: Asahi Glass Company Ltd., Tokyo, Japan (foreign corp.)

APPL-NO: 08/397,052

DATE FILED: Mar. 13, 1995 Jul. 14, 1994 PCT-FILED: PCT-NO:

PCT/JP94/01156 371-DATE: Mar. 13, 1995 Mar. 13, 1995 102(E)-DATE: WO95/02462 PCT-PUB-NO: Jan. 26, 1995 PCT-PUB-DATE:

FRN-PRIOR: Japan 5-197017 Jul. 14, 1993 Japan 5-232516

Aug. 25, 1993 Japan 6-041463 Mar. 11, 1994 Japan 6-092205 Apr. 28, 1994

INT-CL: [6] B32B 27/08; B32B 27/18; B32B 27/28; B32B 31/12

428/335, 421, 422, 446, 447; 524/261, 267, 269, 544, 545, 546; 106/287.1, 287.12; 427/372.2, 387, 393.5 US-CL-ISSUED:

US-CL-CURRENT: 428/335; 106/287.1, 287.12; 427/372.2, 387, 393.5;

428/421, 422, 446, 447; 524/261, 267, 269, 544, 545, 546 SEARCH-FLD:

428/421, 422, 447, 451, 216, 335, 446; 524/261, 267, 269, 412.4, 545, 544, 546, 520; 106/287.16, 287.12, 287.14,

287.13, 287.1; 427/387, 393.5, 372.2

REF-CITED:

U.S. PATENT DOCUMENTS

3,429,845	2/1969	Bechtold et al.	260/29.6
3,575,916	4/1971	Bockstie, Jr.	260/33.4
3,644,260	2/1972	Strolle	260/29.6F
4,028,300	6/1977	Wake et al.	260/31.2R
4,209,432	6/1980	Roth	260/29.2M
4,214,057	7/1980	Ishihara et al.	525/100
4,224,211	9/1980	Kanazawa et al.	260/31.2R
4,732,787	3/1988	Vantillard et al.	427/386
4,751,114	6/1988	Homma et al.	427/407.1
4,781,844	11/1988	Kortmann et al.	252/8.6
5,066,698	11/1991	Hazan et al.	524/269
5,169,915	12/1992	Mohri et al.	526/247
5,216,081	6/1993	Mohri et al.	525/199
5,314,731	5/1994	Yoneda et al.	428/429
5,399,601	3/1995	Kusami et al.	524/188
5,532,304	7/1996	Miyazaki et al.	524/261

173 ART-UNIT:

PRIM-EXMR: Vivian Chen

LEGAL-REP: Oblon, Spivak, McClelland, Maier & Neustadt, P.C.

ABSTRACT:

A method for treating an outdoor article, wherein a surface treating agent comprising a medium (B) containing a tetraalkoxysilane or a silane compound having a silanol group obtained by hydrolyzing an oligomer of such a tetraalkoxy silane (A), wherein the content of (A) is from 0.01 to 100 parts by weight per 100 parts by weight of (B), is used, and a thin film is formed by treating a hydrophobic synthetic resin coating film $\frac{1}{2}$ surface of the outdoor article with such a surface treating agent. It is thereby possible to prevent formation of a streak soils which are likely to form at a portion where rain water collects and runs down, such as below a window frame of a building.

8 Claims, No Drawings

US PAT NO: 5,747,581 [IMAGE AVAILABLE] L4: 6 of 24

DATE ISSUED: May 5, 1998

TITLE: Adhesive and sealing material

Manfred Proebster, Friedrich-Ebert-Str. 4, 69226 Nussloch, INVENTOR:

Federal Republic of Germany

Manfred Schumann, Burgstr. 24, 69121 Heidelberg, Federal

Republic of Germany

APPL-NO: 08/564,363 Dec. 21, 199 Jun. 21, 199 DATE FILED: PCT-FILED: PCT/EP93/01584 PCT-NO: Dec. 21, 1995 Dec. 21, 1995 371-DATE: 102(E)-DATE: WO95/00572 PCT-PUB-NO: Jan. 5, 1995

INT-CL: [6] C08J 3/00; C08K 3/20; C08L 78/00; B65C 9/25

US-CL-ISSUED: 524/590; 156/320, 331.4, 331.7; 427/208.2, 372.2, 385.5, 388.1, 389.7; 524/589; 525/440, 457
US-CL-CURRENT: 524/590; 156/320, 331.4, 331.7; 427/208.2, 372.2, 385.5,

388.1, 389.7; 524/589; 525/440, 457

524/589, 590; 525/440, 457; 427/208.2, 372.2, 385.5, 388.1, 389.7; 156/320, 331.4, 331.7 SEARCH-FLD:

REF-CITED:

PCT-PUB-DATE:

U.S. PATENT DOCUMENTS

3,971,751	7/1976	Isayama et al.	260/37
4,352,858	10/1982	Stanley	428/423.1
4,672,100	6/1987	Schoenbaechler et al.	528/75
4,778,845	10/1988	Tschan et al.	524/710
4,780,520	10/1988	Rizk et al.	528/53
5,155,180	10/1992	Takada et al.	525/440

ECDETCH DAMENIE DOCUMENIES

	F.O.	REIGN PATENT DOCUMENTS
153456	9/1985	European Patent Office
217289	4/1987	European Patent Office
255572	2/1988	European Patent Office
281905	9/1988	European Patent Office
310704	4/1989	European Patent Office
317012	4/1989	European Patent Office
244608	11/1989	European Patent Office
340906	11/1989	European Patent Office
351728	1/1990	European Patent Office
340164	5/1990	European Patent Office
369607	5/1990	European Patent Office
455400	11/1991	European Patent Office
3140884	6/1982	Federal Republic of Germany
3909127	10/1990	Federal Republic of Germany
4023801	1/1991	Federal Republic of Germany
4023804	1/1991	Federal Republic of Germany
4210277	9/1993	Federal Republic of Germany
2234516	2/1991	United Kingdom

ART-UNIT: 151

PRIM-EXMR: Patrick Niland

LEGAL-REP: Ernest G. Szoke, Wayne C. Jaeschke, Real J. Grandmaison

ABSTRACT:

An adhesive and sealing material contains a) at least one reactive prepolymer which is liquid at room temperature and b) at least one further component which is solid at room temperature, liquid at a slightly raised temperature and at least partially incompatible with the liquid prepolymer(s). Component b) is preferably liquid at a temperature of max. 50.degree. C.

17 Claims, 1 Drawing Figures

5,118,532 [IMAGE AVAILABLE] US PAT NO: L4: 10 of 24

DATE ISSUED: Jun. 2, 1992

TITLE: Method of producing decorative vertical louver window

covering material and decorative vertical louver

material so produced

INVENTOR: Ann H. Batson, Anderson, SC

> J. Bennett Billings, Starr, SC D. Gregory Royster, Belton, SC

VyTech Industries, Inc., Anderson, SC (U.S. corp.) ASSIGNEE:

APPL-NO: 07/662,285 DATE FILED: Feb. 28, 1991

Continuation-in-part of Ser. No. 485,608, Feb 27, 1990, REL-US-DATA:

abandoned

INT-CL: [5] B05D 3/0 B05D 5/00 US-CL-ISSUED: 427/278, 316, 365, 393.5, 398.1; 428/290 US-CL-CURRENT: 427/278, 316, 365, 393.5, 398.1; 442/103, 136 SEARCH-FLD: 427/209, 278, 340, 341, 389, 316, 393.5, 398.1, 365;

428/290

REF-CITED:

U.S. PATENT DOCUMENTS

3,844,813 10/1974 Leonard et al. 118/118 X 4,062,989 12/1977 Long 427/176 4,312,914 1/1982 Guth 428/290 Rosamilia et al. 4,590,102 5/1986 427/374.1 4,595,617 6/1986 Bogdany 428/95

139 ART-UNIT:

PRIM-EXMR: Michael Lusignan LEGAL-REP: Dority & Manning

ABSTRACT:

A method of producing decorative web from nonwoven polyester web includes heat setting the web at a temperature between 390 and 410 degrees Farenheit before applying a pigmented, solvent soluble, thermoplastic resin composition to at least one side of the web. The composition can include a polymer solution, which includes a vinyl polymer such as one or both of a polyvinyl chloride homopolymer resin and a polyvinyl chloride acetate copolymer resin, a solvent, plasticizers, heat stabilizers, light stabilizers, pigments and antistats. The composition also preferably may include fillers, soil repellents, and flame retardants. The composition is applied by a knife-over-roll apparatus, a rotogravure printer, or other conventional applicating apparatus. After the composition is applied, the web is passed through a hot air oven maintained at a temperature in the range of from about 230.degree. F. to about 330.degree. F. to dry the web of solvent and cure the composition to form solids in the web. The web can be embossed by passing the web through a conventional embossing apparatus that has been specially modified to include a backup roll to the embossing roll wherein the Shore A hardness of the backup roll is at least 90. The web so produced has a basis weight in the range of from about 3.5 ounces per square yard to about 15 ounces per square yard and includes cured composition solids which include a polyvinyl chloride/vinyl acetate copolymer resin, a polyvinyl chloride resin, plasticizers, stabilizers, antistats, and pigments. Applying standard commercial acceptance tests for louver material, the maximum shrinkage was 1/16", maximum stretch was 1/16", the maximum twist was 5 degrees, lightfastness was at least 200 hours, and no waviness, cupping, crocking or unacceptable mottling was observed.

16 Claims, 6 Drawing Figures

US PAT NO: 5,073,407 [IMAGE AVAILABLE] L4: 12 of 24

DATE ISSUED: Dec. 17, 1991

TITLE: Method of treating a surface Richard Frazer, Williamsville, NY INVENTOR:

Crescent Marketing, Inc., Eden, NY (U.S. corp.) ASSIGNEE:

07/552,702 APPL-NO: DATE FILED:

Jul. 13, 1990 [5] B05D 5/00; B05D 3/12 INT-CL:

US-CL-ISSUED: 427/160, 165, 322, 327, 355, 369, 384, 421, 168 US-CL-CURRENT: 427/160, 165, 168, 322, 327, 355, 369, 384, 421 SEARCH-FLD: 427/160, 369, 327, 322, 421, 355, 384, 165

REF-CITED:

U.S. PATENT DOCUMENTS

3,104,175 9/1963 Marx et al. 427/160 4,218,250 8/1980 Kasprzak 106/3 4,622,246 11/1986 Takeuchi 427/348 4,781,946 11/1988 Takeuchi 427/327 4,900,592 2/1990 Hahn 427/385.5 4,913,967 Bilhorn 4/1990 427/369

139 ART-UNIT:

PRIM-EXMR: Janyce Bell LEGAL-REP: Grimes & Battersby

ABSTRACT:

A method of treating a painted vehicle or glass to form a film which protects the surface and can be easily cleaned. A treatment solution including a surfactant mixed with water is rubbed into sections of the surface being protected until a tacky residue forms on the surface. The tacky residue is then rubbed into the surface until the surface is wiped free of any streaks.

21 Claims, No Drawings

US PAT NO:

4,978,708 [IMAGE AVAILABLE]

L4: 14 of 24

DATE ISSUED:

Dec. 18, 1990

TITLE:

Aqueous-based coating compositions comprising anionic

polyurethane principal resin and anionic acrylic grind

INVENTOR:

Chris W. Fowler, Walled Lake, MI Michael C. Knight, Centerline, MI Anthony J. Nicholas, Clawson, MI

ASSIGNEE:

BASF Corporation, Clifton, NJ (U.S. corp.)

APPL-NO: DATE FILED:

07/343,119 Apr. 25, 1989

INT-CL:

[5] C08L 75/04 US-CL-ISSUED: 524/507; 427/409, 435, 372.2, 407.1; 428/460, 458, 423.1

US-CL-CURRENT: 524/507; 427/372.2, 407.1, 409, 435; 428/423.1, 458, 460 524/507; 427/407.1, 409, 435, 372.2; 428/460, 458, 423.1

REF-CITED:

U.S. PATENT DOCUMENTS

4,007,306	2/1977	Poy et al.	427/377
4,791,168	12/1988	Salatin et al.	524/601
4,794,147	12/1988	Savino et al.	525/440
4,914,148	4/1990	Hille et al.	524/507

ART-UNIT:

158

PRIM-EXMR: Edith Buffalow LEGAL-REP: Jerry F. Janssen

ABSTRACT:

Aqueous-based basecoat compositions, useful for application to metal and/or plastic substrates, comprise an anionic polyurethane principal resin and an anionic acrylic pigment grind resin. The compositions are particularly adapted to application to substrates over a wide range of ambient humidities and have quick drying characteristics. The incorporation of an anionic acrylic grind resin, which is compatible with the anionic polyurethane principal resin, produces a coating which has good pigment wetting and dispersion characteristics with improved shelf life and color stability.

22 Claims, No Drawings

- 441, 442, 447, 451, 494, 517, 520, 521, 522 [IMAGE AVAILABLE]

 16. 4,299,069, Nov. 10, 198. Prefabricated wall facing panel, Alfred Neumann, 52/309.4, 314, 509, 592.6 [IMAGE AVAILABLE]
- 17. 4,164,598, Aug. 14, 1979, Veneer wall covering and method of assembly; William D. Wilhelm, 428/48; 52/306, 309.1, 314; 428/15, 703 [IMAGE AVAILABLE]
- 18. 4,074,480, Feb. 21, 1978, Kit for <u>converting</u> single-glazed window to double-glazed window; Henry W. G. Burton, 52/127.1, 172, 202, 209, 717.02, 786.13; 428/34 [IMAGE AVAILABLE]
 - 19. 3,882,218, May 6, 1975, Brick textured building panels and their method of manufacture and installation; Charles G. Bixel, Jr., 264/157; 52/314, 746.12, DIG.3; 264/129, 293, 321; 428/15 [IMAGE AVAILABLE]

- => muntin/ti,ab,clm
- L1 70 MUNTIN/TI, AB, CLM
- => 11 and 427/clas
- L2 0 L1 AND 427/CLAS
- => 427/372.2,384,385.5,388.4,393.5/cclst
- L3 4532 427/372.2,384,385.5,388.4,393.5/CCLST
- => 13 and window/ti,ab,clm
- L4 24 L3 AND WINDOW/TI, AB, CLM
- => d 1- cit
- 5,895,713, Apr. 20, 1999, Method for treating the surface of an outdoor article; Nobuyuki Miyazaki, et al., 428/335; 106/287.1, 287.12; 427/372.2, 387, 393.5; 428/421, 422, 446, 447; 524/261, 267, 269, 544, 545, 546 [IMAGE AVAILABLE]
- 2. 5,869,128, Feb. 9, 1999, Method of manufacturing a substrate with reduced glare, method for manufacturing a display window of a cathode ray tube and to a cathode ray tube having a display window; Gijsbertus H.W.M. Meulendijks, et al., 427/64, 68, 106, 126.2, 126.3, 162, 165, 230, 348, 385.5 [IMAGE AVAILABLE]
- 3. 5,866,199, Feb. 2, 1999, Primer-paint mask composition and methods of use thereof; Ronald Swidler, et al., 427/154, 155, 156, 385.5, 393.6, 407.1, 407.2 [IMAGE AVAILABLE]
- 4. 5,853,895, Dec. 29, 1998, Bonded vehicular glass assemblies utilizing two-component urethanes, and related methods of bonding; Jeffrey A. Lewno, 428/425.6; 52/204.62, 204.69, 208; 156/108; 296/201; 427/372.2, 385.5, 388.1, 389.7 [IMAGE AVAILABLE]
- 5. 5,773,077, Jun. 30, 1998, Abrasion-protective convertible window; Stanley Edmond, 427/155, 163.1, 209, 393.5 [IMAGE AVAILABLE]
- 6. 5,747,581, May 5, 1998, Adhesive and sealing material; Manfred Proebster, et al., 524/590; 156/320, 331.4, 331.7; 427/208.2, 372.2, 385.5, 388.1, 389.7; 524/589; 525/440, 457 [IMAGE AVAILABLE]
- 7. 5,709,715, Jan. 20, 1998, Silicon or silica substrate with a modified surface, process for producing the same, new orthoesters and process for producing the same; Bruno Guidotti, et al., 8/115.51, 120; 427/299, 331, 385.5, 386, 389.7, 389.8, 389.9; 428/365, 404, 405, 406, 409, 428, 429, 446, 543; 568/595 [IMAGE AVAILABLE]
- 8. 5,705,232, Jan. 6, 1998, In-situ coat, bake and cure of dielectric material processing system for semiconductor manufacturing; Ming Hwang, et al., 427/512, 240, 385.5, 498, 508, 521, 542; 438/782 [IMAGE AVAILABLE]
- 9. 5,597,613, Jan. 28, 1997, Scale-up process for replicating large area diffractive optical elements; Lynn Galarneau, et al., 427/162, 240, 269, 271, 358, 369, 371, 385.5, 389.7, 510 [IMAGE AVAILABLE]
- 10. 5,118,532, Jun. 2, 1992, Method of producing decorative vertical louver window covering material and decorative vertical louver material so produced; Ann H. Batson, et al., 427/278, 316, 365, 393.5, 398.1;

- 11. 5,091,214, Feb. 25, 19., Process for the production of layer of self-cicatrizing polyurethane, and products obtained; Rene Muller, et al., 427/164, 165, 389.7, 393.5; 428/38, 423.1, 425.6 [IMAGE AVAILABLE]
- 12. 5,073,407, Dec. 17, 1991, Method of treating a surface; Richard Frazer, 427/160, 165, 168, 322, 327, 355, 369, 384, 421 [IMAGE AVAILABLE]
- 13. 5,008,154, Apr. 16, 1991, Composition and method for priming and coating silicone substrates; Michael D. Meddaugh, 428/447; 427/302, 322, 387, 393.5, 412.1, 444 [IMAGE AVAILABLE]
- 14. 4,978,708, Dec. 18, 1990, Aqueous-based coating compositions comprising anionic polyurethane principal resin and anionic acrylic grind resin; Chris W. Fowler, et al., 524/507; 427/372.2, 407.1, 409, 435; 428/423.1, 458, 460 [IMAGE AVAILABLE]
- 15. 4,915,763, Apr. 10, 1990, Non-woven fabric, opaque and non-opaque, with and without weave-like finish and process for producing these; Paul G. Swiszcz, 156/209, 219, 220, 263, 290, 291; 160/DIG.7; 427/271, 322, 385.5, 430.1; 428/172 [IMAGE AVAILABLE]
- 16. RE 32,757, Sep. 27, 1988, Glass-run for window glass of motor car; Yoshio Yamazaki, et al., 428/423.1; 49/441; 427/385.5, 393.6; 428/423.9, 424.2; 524/507 [IMAGE AVAILABLE]
- 17. 4,613,540, Sep. 23, 1986, Window for broad bandwidth electromagnetic signal transmission, and method of construction thereof; G. Robert Traut, et al., 428/212; 427/385.5; 428/333, 421, 422 [IMAGE AVAILABLE]
- 18. 4,572,872, Feb. 25, 1986, Glass-run for window glass of motor car; Yoshio Yamazaki, et al., 428/423.1; 49/441; 427/385.5, 393.6; 428/423.9, 424.2; 524/507 [IMAGE AVAILABLE]
- 19. 4,572,871, Feb. 25, 1986, Glass-run for window glass of motor car; Akira Mabuchi, et al., 428/423.1; 49/441; 427/385.5, 393.6; 428/423.9, 424.2; 524/507 [IMAGE AVAILABLE]
- 20. 4,194,022, Mar. 18, 1980, Transparent, colorless, electrically conductive coating; Frank H. Gillery, 427/109, 124, 154, 162, 255.6, 255.7, 331, 343, 384 [IMAGE AVAILABLE]
- 21. 4,145,855, Mar. 27, 1979, System for protecting an enclosed space from high or low temperature extremes; Robert T. Sheldon, 52/232, 79.6, 660, DIG.12; 427/155, 156, 247, 388.4; 428/913 [IMAGE AVAILABLE]
- 22. 4,127,437, Nov. 28, 1978, Process for etching SiO.sub.2 utilizing HF vapor and an organic catalyst; Richard L. Bersin, et al., 438/743; 252/79.1; 427/331, 385.5; 430/313; 438/948 [IMAGE AVAILABLE]
- 23. 3,933,407, Jan. 20, 1976, Articles coated with synergistic anti-fog coatings based on hydrophillic polymers and organosiloxane- oxyalkylene block copolymers; Robert S. Tu, et al., 359/507; 106/13; 215/12.2; 351/62, 159, 166; 359/896; 426/129; 427/162, 164, 165, 387, 389.7, 393.5, 412, 429, 442; 428/412, 447, 483, 510, 516, 520; 525/100, 101 [IMAGE AVAILABLE]
- 24. 3,726,703, Apr. 10, 1973, NON-FOGGING MATERIAL; Ralph William Dornte, 428/412; 106/13; 427/379, 389.7, 393.5; 428/413, 423.1, 524 [IMAGE AVAILABLE]

=> d fro 1,6,10,12,14

US PAT NO: 5,895,713 [IMAGE AVAILABLE] L4: 1 of 24

DATE ISSUED: Apr. 20, 1999

TITLE: Method for treating the surface of an outdoor article

- => outgas?
- L1 4854 OUTGAS?
- => 11 and latex/ti,ab,clm
- L2 18 L1 AND LATEX/TI, AB, CLM
- => 12 and seal?
- L3 8 L2 AND SEAL?
- => 12 not 13
- L4 10 L2 NOT L3
- => d 13 1- cit
- 1. 5,693,714, Dec. 2, 1997, Higher modulus compositions incorporating particulate rubber; Bernard D. Bauman, et al., 525/104; 521/54; 525/129, 169, 184, 222, 232 [IMAGE AVAILABLE]
- 2. 5,581,192, Dec. 3, 1996, Conductive liquid compositions and electrical circuit protection devices comprising conductive liquid compositions; John J. Shea, et al., 324/722, 555; 335/47, 51; 361/58 [IMAGE AVAILABLE]
- 3. 5,506,283, Apr. 9, 1996, Higher modulus compositions incorporating particulate rubber; Edwin L. McInnis, et al., 525/332.8; 521/42.5; 525/332.9, 333.1, 333.2, 356 [IMAGE AVAILABLE]
- 4. 5,500,187, Mar. 19, 1996, Disposable optical agglutination assay device and method for use; James H. Deoms, et al., 422/58, 61, 73; 435/287.1, 287.2, 288.7, 810; 436/164, 165, 514, 531, 534, 536, 538, 541, 805, 807, 815 [IMAGE AVAILABLE]
- 5. 5,280,689, Jan. 25, 1994, Composite cladding panel; Peter A. D. Mill, 52/309.9, 169.14, 235, 314, 796.1 [IMAGE AVAILABLE]
- 6. 3,993,811, Nov. 23, 1976, Thermal insulating panel for use in an insulative container and method of making said panel; Wilhelm E. Walles, 428/35.9; 215/12.2; 220/62.11, 592.27; 427/183, 304; 428/357, 912.2 [IMAGE AVAILABLE]
- 7. 3,921,844, Nov. 25, 1975, Heat insulating container having plastic walls retaining vacuum; Wilhelm E. Walles, 215/13.1; 428/34, 35.9 [IMAGE AVAILABLE]
- 8. 3,828,960, Aug. 13, 1974, HEAT INSULATING CONTAINER HAVING PLASTIC WALLS RETAINING VACUUM; Wilhelm E. Walles, 215/13.1; 428/35.9 [IMAGE AVAILABLE]
- => d 14 1- cit
- 1. 5,454,801, Oct. 3, 1995, Printed polymer coatings and method for making same; Nels J. Lauritzen, 604/378, 358, 367, 381, 387 [IMAGE AVAILABLE]
- 2. 5,419,975, May 30, 1995, Inorganic ceramic paper, its method of manufacture and articles produced therefrom; Timothy S. Lintz, et al., 428/688, 113, 212, 325 [IMAGE AVAILABLE]

- 3. 5,234,804, Aug. 10, 1993 Photographic paper support with liver halide emulsion layer; Erika Sato, et al., 430/538, 531, 539 [IMAGE AVAILABLE]
- 4. 5,075,368, Dec. 24, 1991, Synthetic alkali metal aluminosilicates and use in paints; Salish K. Wason, 524/450; 523/466, 521 [IMAGE AVAILABLE]
- 5. 4,933,387, Jun. 12, 1990, Synthetic alkali metal alumino-silicates, methods and uses, compositions and their methods of preparation; Satish K. Wason, 524/450; 523/466, 521 [IMAGE AVAILABLE]
- 6. H 347, Oct. 6, 1987, Alumina fiber reinforced lithium aluminosilicate; George K. Layden, et al., 428/113, 293.7 [IMAGE AVAILABLE]
- 7. 4,596,834, Jun. 24, 1986, Water resistant foamed product prepared from a latex, a mineral acid, hydraulic cement, filler, aggregate and stabilizer; Joseph Widener, et al., 521/83; 106/672, 692 [IMAGE AVAILABLE]
- 8. 4,182,649, Jan. 8, 1980, Polyurethane foam sheet and method; Irving E. Isgur, et al., 162/101, 108, 155, 168.2, 169, 183; 428/317.9, 327, 402, 423.5, 424.8, 425.1; 442/221, 370 [IMAGE AVAILABLE]
- 9. 4,075,166, Feb. 21, 1978, Method of stabilization of rubbers and vulcanizates; Vladimir Vasilievich Moiseev, et al., 524/239, 240, 249, 925, 926 [IMAGE AVAILABLE]
- 10. 3,646,749, Mar. 7, 1972, MACHINE-WASHABLE METALLIZED FIBROUS ARTICLE AND METHOD OF MAKING SAME; Philip J. Clough, et al., 442/188; 28/166, 169; 139/425R; 427/407.1; 428/378, 381, 394, 413 [IMAGE AVAILABLE]
- => seal?/ti,ab,clm and latex/ti,ab,clm not 13-14
- L5 662 SEAL?/TI,AB,CLM AND LATEX/TI,AB,CLM NOT (L3 OR L4)
- => 15 and 427/clas
- L6 68 L5 AND 427/CLAS
- => sel 1- ccls; d sel e1-e30
- E1 THROUGH E367 ASSIGNED

E#	FILE	FREQUENCY	TERM
E1	USPAT	8	427/407.1/CCLS
E2	USPAT	7	427/2.3/CCLS
E3	USPAT	6	128/844/CCLS
E4	USPAT	6	427/136/CCLS
E5	USPAT	6	427/385.5/CCLS
E6	USPAT	6	427/393.5/CCLS
E7	USPAT	6	427/393.6/CCLS
E8	USPAT	5	2/168/CCLS
E9	USPAT	5	427/140/CCLS
E10	USPAT	5	427/393/CCLS
E11	USPAT	4	427/138/CCLS
E12	USPAT	4	427/203/CCLS
E13	USPAT	3	2/167/CCLS
E14	USPAT	3	264/31/CCLS
E15	USPAT	3	427/264/CCLS
E16	USPAT	3	427/265/CCLS
E17	USPAT	3	427/325/CCLS
E18	USPAT	3	427/373/CCLS
E19	USPAT	3	427/384/CCLS
E20	USPAT	3	427/387/CCLS
E21	USPAT	3	427/388.4/CCLS
E22	USPAT	3	427/408/CCLS

E23 E24 E25 E26 E27 E28 E29	USPAT USPAT USPAT USPAT USPAT USPAT USPAT	3 3 3 3 2	427/412.1/CCLS 427/421/CCLS 427/430.1/CCLS 428/319.7/CCLS 428/327/CCLS 428/446/CCLS 118/405/CCLS
E29	USPAT	2	118/405/CCLS
E30	USPAT		404/82/CCLS

.

- => 52/171.3,172,786.13,456,314/cclst
- L1 1495 52/171.3,172,786.13,456,314/CCLST
- => 11 and latex
- L2 19 L1 AND LATEX
- => d 1- cit
- 1. 5,634,307, Jun. 3, 1997, Imitation stone surface apparatus and method; Jean-Paul Larriberot, et al., 52/314, 316, 318 [IMAGE AVAILABLE]
- 2. 5,493,821, Feb. 27, 1996, Adsorbent for use in double glazed windows; Alan P. Cohen, et al., 52/171.3, 172, 788.1; 428/34 [IMAGE AVAILABLE]
 - 3. 5,305,569, Apr. 26, 1994, Thick shingle; Alfred B. Malmquist, et al., 52/309.8, 309.14, 314, 555, 558, 559, 560 [IMAGE AVAILABLE]
- 5,280,689, Jan. 25, 1994, Composite cladding panel; Peter A. D. Mill, 52/309.9, 169.14, 235, 314, 796.1 [IMAGE AVAILABLE]
- 5. 5,197,242, Mar. 30, 1993, <u>Dual-pane</u> thermal window with <u>liquid</u> crystal shade; Ray H. Baughman, et al., 52/171.3, 786.1; 349/16; 428/34 [IMAGE AVAILABLE]
 - 6.) 5,152,111, Oct. 6, 1992, Dual-pane thermal window with liquid crystal shade; Ray H. Baughman, et al., 52/171.3, 173.3, 786.1; 349/16; 428/34 [IMAGE AVAILABLE]
 - 7. 5,111,629, May 12, 1992, Dual-pane thermal window with liquid crystal shade; Ray H. Baughman, et al., 52/171.3, 786.1 [IMAGE AVAILABLE]
 - 8. 5,025,602, Jun. 25, 1991, Dual-pane thermal window with liquid crystal shade; Ray H. Baughman, et al., 52/171.3; 349/16, 58; 428/34 [IMAGE AVAILABLE]
 - 9. 5,009,044, Apr. 23, 1991, Dual-pane thermal window with liquid crystal shade; Ray H. Baughman, et al., 52/171.3, 786.11; 349/16; 428/34 [IMAGE AVAILABLE]
 - 10. 4,964,251, Oct. 23, 1990, Dual-pane thermal window with liquid crystal shade; Ray H. Baughman, et al., 52/171.3; 349/16; 428/34 [IMAGE AVAILABLE]
 - 11. 4,899,503, Feb. 13, 1990, Dual-pane thermal window with liquid crystal shade; Ray H. Baughman, et al., 52/171.3, 786.11; 349/16; 428/34 [IMAGE AVAILABLE]
 - 12 4,698,891, Oct. 13, 1987, Separator for insulated window glass; Ryszard Borys, 29/417, 429, 458; 52/172, 209, 717.02, 786.13; 156/93, 203, 276, 308.4; 228/147, 176 [IMAGE AVAILABLE]
 - 13. 4,579,613, Apr. 1, 1986, Method for manufacturing of a molded door; Fernand Belanger, 156/78; 52/309.8, 313, 316, 456, 457, 458; 156/228, 244.27; 264/292 [IMAGE AVAILABLE]
 - 14) 4,476,169, Oct. 9, 1984, Multilayer glass structure; Hiroshi Nishino, et al., 428/34; 52/172; 428/404, 407; 502/68 [IMAGE AVAILABLE]
 - 15. 4,348,435, Sep. 7, 1982, Primed multiple glazed units for curtainwall systems; George R. Mistrick, et al., 428/34; 52/786.13; 156/109, 307.3, 307.5, 334; 427/387, 389.7, 393.5, 412.1, 413; 428/429,

=> d 16 1- cit

- 1. 5,849,124, Dec. 15, 1998, Composite flooring system; Joseph A. Rusk, Jr., et al., 156/71, 63, 276; 264/31, 109; 427/203, 218 [IMAGE AVAILABLE]
- 2. 5,817,365, Oct. 6, 1998, Production of rubber articles, such as gloves; Margaret Pamela Richardson, et al., 427/7; 2/167, 168; 264/300, 305, 307, 308; 427/340; 428/916 [IMAGE AVAILABLE]
- 3. 5,788,142, Aug. 4, 1998, Process for joining, coating or repairing parts made of intermetallic material; Yves Bigay, et al., 228/198, 193, 246; 419/8, 45, 54, 55, 68, 69; 427/140, 142, 226 [IMAGE AVAILABLE]
- 4. 5,786,095, Jul. 28, 1998, Inorganic based intumescent system; Vernon H. Batdorf, 428/446; 106/600, 632; 427/372.2, 376.2, 397.7; 428/324, 325, 327, 701, 702, 921 [IMAGE AVAILABLE]
- 5. 5,759,705, Jun. 2, 1998, Stain inhibiting pigment composition; John Sinko, 428/537.1; 427/325, 384, 408 [IMAGE AVAILABLE]
- 6. 5,756,144, May 26, 1998, Medical instrument with a hydrophilic, low-friction coating and method of preparation; Per Wolff, et al., 427/2.3, 2.1, 388.4, 409, 412.1; 428/515 [IMAGE AVAILABLE]
- 7. 5,733,666, Mar. 31, 1998, Aqueous sealer composition for wood surfaces and process; John Sinko, 428/537.1; 427/297, 325, 440 [IMAGE AVAILABLE]
- 8. 5,721,296, Feb. 24, 1998, Asphalt additive and asphalt composition; Tatsuya Mizunuma, et al., 524/60; 427/136, 138; 524/59, 705 [IMAGE AVAILABLE]
- 9. 5,718,943, Feb. 17, 1998, Method for producing efflorescence resistant coating on cementitious substrate; Oscar Hsien-Hsiang Hsu, et al., 427/136, 373, 393.6 [IMAGE AVAILABLE]
- 10. 5,695,823, Dec. 9, 1997, Prepress sealer application technology by foaming; Oscar Hsien-Hsiang Hsu, et al., 427/370, 391, 392, 393 [IMAGE AVAILABLE]
- 11. 5,679,399, Oct. 21, 1997, Method of forming a membrane, especially a latex or polymer membrane, including multiple discrete layers; Robin Renee Thill Shlenker, et al., 427/2.3; 2/168; 128/844; 424/404; 427/407.1 [IMAGE AVAILABLE]
- 12. 5,635,248, Jun. 3, 1997, Method of producing coating on reconstituted wood substrate; Oscar H. Hsu, et al., 427/358; 264/46.4, 113, 120, 241, 255; 427/366, 370, 373, 382, 393, 397 [IMAGE AVAILABLE]
- 13. 5,549,924, Aug. 27, 1996, Method of forming a membrane, especially a latex or polymer membrane, including a deactivating barrier and indicating layer; Robin R. T. Shlenker, et al., 427/2.3; 2/168; 128/844; 424/404; 427/407.1 [IMAGE AVAILABLE]
- 14. 5,534,610, Jul. 9, 1996, Solventless two component primer composition for improved adhesion of RTV silicone elastomers to substrates; Brian P. Bayly, et al., 528/38; 427/407.1; 428/447; 528/21, 33, 37; 556/425 [IMAGE AVAILABLE]
- 15. 5,447,752, Sep. 5, 1995, Method for making a decorative cementitous pattern on a surface; Clyde T. Cobb, 427/270; 264/31, DIG.31; 427/140, 272, 277, 278, 282 [IMAGE AVAILABLE]

- 16. 5,427,819, Jun. 27, 1995. Corrosion inhibiting repair and rehabilitation treatment prosing some for reinforced concrete structures; Richard E. Weyers, et al., 42,/136, 140, 264, 265, 292, 384, 357.8, 403 [IMAGE AVAILABLE]
- 17. 5,380,694, Jan. 10, 1995, Thermosensitive recording element; Robert R. Krebs, 503/214; 427/152; 503/200, 226 [IMAGE AVAILABLE]
- 18. 5,372,858, Dec. 13, 1994, Method and apparatus for applying a plastic coating to woven yarn tubing; Frank D. Saylor, III, 427/512; 118/65, 67, 68, 405, 419, 423; 427/322, 385.5, 412, 434.7, 513, 521, 559 [IMAGE AVAILABLE]
 - 19. 5,344,688, Sep. 6, 1994, Coated abrasive article and a method of making same; Jeffrey S. Peterson, et al., 428/102; 51/298, 309; 427/203, 487, 493, 513, 532, 553, 558; 442/69, 73 [IMAGE AVAILABLE]
 - 20. 5,344,675, Sep. 6, 1994, Emulsion polymer blend; Barry S. Snyder, 427/388.4, 389, 389.7, 391, 393, 393.5, 393.6; 523/201 [IMAGE AVAILABLE]
 - 21. 5,330,795, Jul. 19, 1994, Emulsion based coatings and a method using an emulsion based coating to seal asbestos containing soils; Vern H. Batdorf, et al., 427/393.6, 136, 299, 421 [IMAGE AVAILABLE]
 - 22. 5,244,623, Sep. 14, 1993, Method for isostatic pressing of formed powder, porous powder compact, and composite intermediates; Alan G. King, 264/510, 219, 317, 570; 419/42; 427/226, 299, 385.5, 430.1 [IMAGE AVAILABLE]
 - 23. 5,223,309, Jun. 29, 1993, Ion implantation of silicone rubber; Robert S. Farivar, et al., 427/525, 296, 527 [IMAGE AVAILABLE]
 - 24. 5,151,456, Sep. 29, 1992, Emulsified sealant having a high solids content; Samir F. Elias, et al., 524/60; 106/277; 427/138, 208.8; 516/43, 46; 524/68 [IMAGE AVAILABLE]
 - 5,130,159, Jul. 14, 1992, Membranes fashioned from latex and other materials and methods of producing the same; Robin R. T. Shlenker, et al., 427/2.3; 2/167, 168; 128/844; 523/122 [IMAGE AVAILABLE]
 - 26. 5,122,390, Jun. 16, 1992, Method for uniformly coating a probe with dielectric and assembling a coax-to-waveguide transition; Charles C. Rearick, et al., 427/117; 333/26, 158; 427/58, 127, 430.1, 434.6 [IMAGE AVAILABLE]
 - 27. 5,113,874, May 19, 1992, Membranes useful in preparing prophylactic devices having pathogen resistant barriers, and flexible electrodes; Hovaness H. Maronian, 128/844; 264/83; 427/2.3; 604/347 [IMAGE AVAILABLE]
 - 28. 5,091,229, Feb. 25, 1992, Electronics protective packaging film; Ralph C. Golike, et al., 428/35.2; 206/524, 720, 721; 252/512; 427/215; 428/403, 404, 570 [IMAGE AVAILABLE]
 - 29. 5,069,227, Dec. 3, 1991, Prophylactic device having pathogen resistant barrier; Hovaness Maronian, 128/844; 427/2.3 [IMAGE AVAILABLE]
 - 30. 5,059,264, Oct. 22, 1991, Aqueous inpress primer sealer for hardboard manufacturing; Harold J. Sheets, 156/62.2; 427/393; 428/151 [IMAGE AVAILABLE]
 - 31. 5,045,341, Sep. 3, 1991, Covering such as a suit, glove, condom or sheath forming a chemical barrier against harmful agents and methods of making the same; Robin R. T. Shlenker, 128/844; 2/167, 168; 427/2.3; 428/321.1; 604/349 [IMAGE AVAILABLE]
 - 32. 5,030,482, Jul. 9, 1991, Filter gasketing; Fereshteh Tadayon, 427/244, 284, 294, 430.1 [IMAGE AVAILABLE]
 - 33. 4,979,378, Dec. 25, 1990, Costume jewelry method of making costume

- jewelry from cotton burrs; Cathy M. Cardin, et al., 63/36; 29/458, 896.41; 63/12, 20; 427/4, 32 407.1; 428/10, 17, 28 [IMAGE ALABLE]
- 34. 4,897,302, Jan. 30, 1990, Sporting surfaces; Paul F. Bull, 442/395; 427/212, 407.1, 407.3; 428/17, 95, 295.1, 304.4, 317.9, 327; 442/417 [IMAGE AVAILABLE]
- 35. 4,816,259, Mar. 28, 1989, Process for coating gelatin capsules; James W. Matthews, et al., 424/463; 427/2.18, 2.19, 2.2, 214, 220, 221 [IMAGE AVAILABLE]
- 36. 4,806,390, Feb. 21, 1989, Masking compositions for chemical milling and method for applying the same; Fred D. Hawker, et al., 427/156, 259, 327, 388.4, 409, 435; 524/446, 519 [IMAGE AVAILABLE]
- 37. 4,768,561, Sep. 6, 1988, Process for sealing pipes; Sadahisa Hyodo, et al., 138/97; 137/15; 427/230 [IMAGE AVAILABLE]
- 38. 4,762,731, Aug. 9, 1988, Barrier film structures using carbon monoxide-containing polymers; Gerald M. Lancaster, et al., 427/536, 208.2, 385.5, 516; 428/347, 349 [IMAGE AVAILABLE]
- 39. 4,744,328, May 17, 1988, Sealant compositions and methods for use in detecting equipment tampering; D. Lynn Stevens, et al., 116/200, 212; 285/80; 292/307R; 427/7 [IMAGE AVAILABLE]
- 40. 4,729,919, Mar. 8, 1988, Protective barrier coating for styrofoam using an unsaturated thermosettable resin composition; James C. Uroda, 428/215; 427/203, 412.1; 428/319.3, 319.7, 519, 520 [IMAGE AVAILABLE]
- 41. 4,671,040, Jun. 9, 1987, Method for flameproofing shingled surfaces; Charles H. Braithwaite, Jr., 52/748.1; 427/260, 261, 284, 286 [IMAGE AVAILABLE]
- 42. 4,657,772, Apr. 14, 1987, Introducer sheath assembly; Nuri Kocak, 427/2.28, 387, 388.5, 435 [IMAGE AVAILABLE]
- 43 4,656,796, Apr. 14, 1987, Building structure and method of producing the same; Pietro De Porcellinis, 52/169.7, 741.12, 742.12; 166/295; 427/372.2 [IMAGE AVAILABLE]
- 44. 4,652,395, Mar. 24, 1987, Taggant composition; George L. Marcina, et al., 252/301.35; 250/302, 462.1; 252/301.16, 301.34, 301.36; 427/157 [IMAGE AVAILABLE]
- 45. 4,634,395, Jan. 6, 1987, Inflatable elastomeric balloons having increased buoyant lifetimes; Donald Burchett, 446/222; 427/230, 231; 428/12, 492; 446/220 [IMAGE AVAILABLE]
- 46.) 4,627,999, Dec. 9, 1986, Process for prefinished exterior hardboard; Tracy C. Hsu, 428/326; 427/393, 393.4, 393.5, 408, 412.2; 428/327 [IMAGE AVAILABLE]
- 47. 4,610,919, Sep. 9, 1986, Binder for fibrous padding; James Kent, 442/149; 427/421; 442/168; 524/513, 514 [IMAGE AVAILABLE]
- 48. 4,581,255, Apr. 8, 1986, Method of making simulated ceramic tile; William G. Coggan, et al., 427/264, 265, 270, 280, 325, 408; 428/49 [IMAGE AVAILABLE]
- 49. 4,563,491, Jan. 7, 1986, Stucco coating composition; Michele Comune, 524/47; 427/403; 524/413, 425, 432, 492 [IMAGE AVAILABLE]
- 50. 4,529,622, Jul. 16, 1985, Method for constructing all-weather surface; Marvin L. Maxfield, 427/136, 138, 203, 379, 393.6, 407.1, 421 [IMAGE AVAILABLE]
- 51. 4,505,951, Mar. 19, 1985, Method for making a polyvinylidene chloride coated biaxially oriented polyethylene terephthalate container;

- Leo J. Kennedy, 427/542, 374_1. 393.5; 428/36.6, 483 [IMAGE AXAILABLE]
- 52. 4,464,423, Aug. 7, 1984, Method for forming dual gloss coacing; Michael H. LaBianca, et al., 427/244, 261, 264, 265, 373 [IMAGE AVAILABLE]
- 53. 4,392,335, Jul. 12, 1983, Flexible cementitious coatings; Robert B. Heiman, 52/309.17, 514, 741.4; 404/17, 82; 427/136; 428/413, 446, 703 [IMAGE AVAILABLE]
- 54. 4,380,595, Apr. 19, 1983, Encapsulating sealant compositions for friable insulation materials; John Arpin, 524/5; 427/221, 387, 393.6, 407.1; 428/404; 524/442 [IMAGE AVAILABLE]
- 55. 4,348,435, Sep. 7, 1982, Primed multiple <u>glazed units</u> for curtainwall systems; George R. Mistrick, et al., 428/34; 52/786.13; 156/109, 307.3, 307.5, 334; 427/387, 389.7, 393.5, 412.1, 413; 428/429, 441, 442, 447, 451, 494, 517, 520, 521, 522 [IMAGE AVAILABLE]
- 56. 4,306,729, Dec. 22, 1981, Sealing material; Fumio Hiramatsu, et al., 277/570, 936, 944; 427/290 [IMAGE AVAILABLE]
- 4,289,805, Sep. 15, 1981, Method for sealing porosity leaks in pneumatic tires; Jerome Dubow, 427/140, 231 [IMAGE AVAILABLE]
 - 58. 4,268,428, May 19, 1981, Asphaltic material and method; Robert R. Green, 524/71; 427/138, 140, 393.6 [IMAGE AVAILABLE]
 - 59. 4,259,379, Mar. 31, 1981, Application of liquid material to webs; Arthur Britton, et al., 427/356; 118/125, 126, 404, 405, 413, 415; 427/365, 385.5, 394, 434.2, 434.7 [IMAGE AVAILABLE]
- 60) 4,239,541, Dec. 16, 1980, Mildew sealing coating composition and method of using; Emanuel F. Marek, et al., 106/15.05, 18.33, 18.34; 427/374.1, 385.5, 407.1, 419.1, 419.2, 419.3; 428/907; 523/122 [IMAGE AVAILABLE]
 - 61. 4,188,414, Feb. 12, 1980, Method for applying sealing material to envelopes; Robert Cohn, 427/541; 53/381.7, 383.1; 156/442.1; 229/80; 427/285, 543 [IMAGE AVAILABLE]
 - 62. 4,075,374, Feb. 21, 1978, Floor preparation and method; Clyde R. Jorgenson, et al., 427/355; 52/309.17; 106/735; 264/31; 404/72, 82, 97, 101; 524/2, 8, 423 [IMAGE AVAILABLE]
- 63. 4,022,943, May 10, 1977, Sheet type covering material with metallic luster and process for making same; Edward R. Erb, et al., 428/159; 264/DIG.82; 427/258; 428/164, 203, 213, 319.7 [IMAGE AVAILABLE]
- 64. 4,018,957, Apr. 19, 1977, Coated fabric sheet-type material having resilient backing and process for making same; Jesse Werner, et al., 428/141; 427/209, 381, 389.9, 412; 428/159, 160, 161, 162, 319.7, 332; 442/226 [IMAGE AVAILABLE]
- 65) 3,967,012, Jun. 29, 1976, Method of making a sealing and insulating coating; Jakob Ebner, 427/380, 379; 428/446, 451, 462, 465 [IMAGE AVAILABLE]
- 66. 3,936,560, Feb. 3, 1976, Self-sealable corrosion protectable packaging material and method of making; Pasco R. Santurri, et al., 428/219; 106/14.37, 14.39; 252/390, 392; 422/8, 9; 427/208.4, 208.8, 384, 385.5, 401, 412.3, 412.5; 428/34.3, 35.2, 35.3, 220, 423.3, 423.5, 423.7, 424.2, 424.4, 424.6, 424.7, 424.8, 425.3, 475.2, 476.9, 480, 483, 492, 515, 516 [IMAGE AVAILABLE]
- 67. 3,853,660, Dec. 10, 1974, PROCESSES RELATING TO SENSIBLE COATINGS AND TRANSFER RIBBONS FOR PLASTIC CARDS THERETO; Gary J. Peters, et al., 156/230, 247, 312; 427/256, 393.5 [IMAGE AVAILABLE]

=> 15 and 264/clas not 16

42 L5 AND 264/CLAS NOT L6

=> d 1- cit

L7

- 1. 5,830,396, Nov. 3, 1998, Method for processing thermoplastics, thermosets and elastomers; Joel C. Higgins, et al., 264/109, 120, 122, 320 [IMAGE AVAILABLE]
- 2. 5,819,394, Oct. 13, 1998, Method of making board matched nested support fixture; Mark Curtin, 29/527.2, 760; 264/272.11, 272.17 [IMAGE AVAILABLE]
- 3. 5,792,403, Aug. 11, 1998, Method of molding green bodies; Ted R. Massa, et al., 264/122, 313, 570; 419/68 [IMAGE AVAILABLE]
- 4. 5,766,525, Jun. 16, 1998, Methods for manufacturing articles from sheets of unhardened hydraulically settable compositions; Per Just Andersen, et al., 264/40.1, 42, 102, 129, 132, 138, 157, 175 [IMAGE AVAILABLE]
- 5. 5,762,843, Jun. 9, 1998, Method of making composite cermet articles; Ted R. Massa, et al., 264/122; 419/10, 12, 13, 14, 15, 16, 17, 18, 19, 23 [IMAGE AVAILABLE]
- 6. 5,676,905, Oct. 14, 1997, Methods for manufacturing articles of manufacture from hydraulically settable mixtures; Per Just Andersen, et al., 264/426, 42, 54, 82, 102, 232, 234, 239, 299, 328.1, 328.2, 333, 340, 344 [IMAGE AVAILABLE]
- 7. 5,486,322, Jan. 23, 1996, Production of multilayer productive coverings on conventional dip molding lines; Ingbert E. Fuchs, 264/46.5, 54, 300, 301, 305, 307, 308 [IMAGE AVAILABLE]
- 8. 5,391,019, Feb. 21, 1995, Environmental enclosure structure and method of manufacture; J. P. Pat Morgan, 405/128; 52/659; 264/256; 405/52; 588/249 [IMAGE AVAILABLE]
- 9. 5,387,380, Feb. 7, 1995, Three-dimensional printing techniques; Michael Cima, et al., 264/69, 109, 123, 128, 308; 347/1; 425/130, 218, 425 [IMAGE AVAILABLE]
- 10. 5,215,701, Jun. 1, 1993, Process for making a surgical glove; Arnold S. Gould, et al., 264/331.13, 255, 299, 301 [IMAGE AVAILABLE]
- 11. 5,209,603, May 11, 1993, Secondary containment structure and method of manufacture; J. P. Pat Morgan, 405/52; 52/659; 264/256; 405/55 [IMAGE AVAILABLE]
- 12. 5,108,686, Apr. 28, 1992, Method of replicating a human nipple for use as a nursing device; Joyce B. Griffin, 264/222; 215/11.1; 264/138, 227, 255; 606/236 [IMAGE AVAILABLE]
- 13. 5,059,486, Oct. 22, 1991, Self-Healing rubber article and method; Hovaness H. Maronian, et al., 428/493; 264/288.4, 289.6, 291 [IMAGE AVAILABLE]
- 14. 5,043,119, Aug. 27, 1991, High strength particulate ceramics; Kenneth J. Liles, et al., 264/667, 125, 668; 501/98.6 [IMAGE AVAILABLE]
- 15. 4,999,157, Mar. 12, 1991, Method for molding powders; Hiroaki Nishio, et al., 419/68; 249/65, 112, 127, 183; 264/102, 219, 220, 571, DIG.78; 419/60, 66; 425/405.1, 405.2, DIG.14 [IMAGE AVAILABLE]

- 16. 4,761,264, Aug. 2, 1988, Method for molding powders; Hiroaki Nishio, et al., 419/68; 249/65, 112, 7; 264/102, 220, 571, DIG.78; 60, 66; 425/405.1, 405.2, DIG.14 [IMALE AVAILABLE]
- 17. 4,698,887, Oct. 13, 1987, Method for fabricating thermally insulated pipeline section; Farrokh A. Patell, et al., 29/890.14, 458, 527.1, DIG.29; 264/45.3 [IMAGE AVAILABLE]
- 18. 4,681,803, Jul. 21, 1987, Pigmented, heat-sealable coating composition for application to oriented polyolefin films; Leland L. Liu, 428/348; 106/272; 264/171.24, 173.14, 290.2; 428/317.9, 349, 484, 515, 516, 518; 524/277 [IMAGE AVAILABLE]

. 4

- 19. 4,668,451, May 26, 1987, Process of making a full life size artificial rock formation from a natural rock formation surface; Bruce K. Langson, 264/39, 220, 225, 245, 256, 308, 309, 313, 510, 571, DIG.78; 428/15 [IMAGE AVAILABLE]
- 20. 4,643,862, Feb. 17, 1987, Refractory stove damper with catalytic effect; Earnest J. Callahan, 264/133; 110/163, 203; 126/285R, 292; 264/232, 333 [IMAGE AVAILABLE]
- 21. 4,639,283, Jan. 27, 1987, Method for making a diaphragm for an electro-acoustic transducer; Akira Nakamura, 156/89.13; 181/167; 264/44, 129, 136, 137, 317, DIG.44 [IMAGE AVAILABLE]
- 22. 4,637,789, Jan. 20, 1987, Cushion fabrication apparatus; Frederick P. Netznik, 425/89; 249/112, 158, 167; 264/46.8, 101, 316; 425/112, 117, 388, 817R [IMAGE AVAILABLE]
- 23. 4,537,133, Aug. 27, 1985, Non-incendive rock-breaking explosive charge; Richard J. Mainiero, 102/316; 86/20.15; 102/290, 321, 323, 331, 332; 264/3.1 [IMAGE AVAILABLE]
- 24. 4,477,504, Oct. 16, 1984, Utilization of plastic films to control gas pressure and reduce foam in cellular foam products; Larry E. Bailey, et al., 428/138; 264/46.8; 428/159, 160, 318.8, 319.7 [IMAGE AVAILABLE]
- 25. 4,415,548, Nov. 15, 1983, Spermicidally lubricated prophylactics and method for making same; K. Prakash Reddy, 128/844; 53/428, 431; 206/69; 264/129, 301, 334; 424/404, 414; 604/289, 349 [IMAGE AVAILABLE]
- 26. 4,360,994, Nov. 30, 1982, Concrete crack sealing system; Bonnie E. Hodges, 52/742.16; 264/36.2, 36.22 [IMAGE AVAILABLE]
- 27. 4,344,909, Aug. 17, 1982, Thermochromic composition; Francis J. A. M. C. De Blauwe, 264/230; 53/442; 116/207, 216; 138/104; 264/DIG.71; 285/41, 93, 187, 381.4; 374/45, 162; 422/61; 428/34.9, 913 [IMAGE AVAILABLE]
- 28. 4,327,046, Apr. 27, 1982, Method for producing a rigid, shaped mass support system; Thomas A. Davis, et al., 264/102, 122, 129, 222, DIG.7; 428/323 [IMAGE AVAILABLE]
- 29. 4,306,549, Dec. 22, 1981, Splint-cast; Joseph G. Canie, 602/8; 264/102, 222 [IMAGE AVAILABLE]
- 30. 4,293,126, Oct. 6, 1981, Leg weights; Donald F. Havens, 482/105; 156/213, 300; 264/273; 482/55 [IMAGE AVAILABLE]
- 31. RE 30,378, Aug. 19, 1980, Process for recovery of polymers from their dispersions in liquids; Archie R. Bice, et al., 528/486; 159/2.2; 264/86, 349; 366/85; 528/494, 502F, 931, 936 [IMAGE AVAILABLE]
- 32. 4,195,050, Mar. 25, 1980, Method for making a filter; Peter A. Walther, 264/137, 46.6, 138, 255, 261, 263 [IMAGE AVAILABLE]
- (33) 4,148,991, Apr. 10, 1979, Method of coagulating polymer latex emulsions; Richard H. Skidmore, 528/502C; 264/349; 528/499 [IMAGE

- 34. 4,143,452, Mar. 13, 1979, Pacifier method of construction; Louise Z. Hakim, 29/434, 453; 156/245, 293; 264/263, 275, 299; 606/236 [IMAGE AVAILABLE]
- 35. 4,136,251, Jan. 23, 1979, Extrusion process for recovery of polymers from their dispersions in liquids; Archie R. Bice, et al., 528/486; 159/2.2; 264/86, 349; 366/85; 528/494, 502F, 931 [IMAGE AVAILABLE]
- 36. 4,133,623, Jan. 9, 1979, Production of rubber tubing from latex; Alfred R. Bevan, et al., 425/133.1; 264/209.1; 425/200, 379.1, 380, 467, 812 [IMAGE AVAILABLE]
- 37. 4,100,006, Jul. 11, 1978, Card-clothing; John Buckley, 156/78; 19/114; 156/91, 250; 264/46.4, 50; 428/319.7 [IMAGE AVAILABLE]
- 38. 4,064,301, Dec. 20, 1977, Floral base; John H. Howard, 428/151; 47/41.01; 156/257, 278; 264/129, 162, 321, DIG.14; 428/3, 23, 167, 314.2, 314.8 [IMAGE AVAILABLE]
- 39. 3,993,292, Nov. 23, 1976, Apparatus for coagulating polymer latex emulsions; Richard H. Skidmore, 366/87; 159/2.2; 264/349 [IMAGE AVAILABLE]
 - 40. 3,917,771, Nov. 4, 1975, Sealant filler for small volumes containing an acrylic latex, sand, bentonite, portland cement and a polyhydric alcohol; Mario J. Basile, 264/35; 106/778; 264/36.2, 36.22; 524/5 [IMAGE AVAILABLE]
 - 41. 3,843,586, Oct. 22, 1974, PROCESS FOR PREPARING A FOAMABLE MATERIAL FOR SEALING RUBBER ARTICLES UPON PRESSURE REDUCTION THEREOF; Johannes Hendrik Leendert Wolf, 206/302; 141/38; 264/36.14, 46.4; 516/18, 917; 521/71, 72, 82, 150; 524/903 [IMAGE AVAILABLE]
 - 42. 3,742,093, Jun. 26, 1973, METHOD OF SEPARATING AN INSOLUBLE LIQUID FROM POLYMER COMPOSITION; Richard H. Skidmore, 525/197; 159/2.2; 210/808; 264/349; 525/232; 528/501, 502C, 502F [IMAGE AVAILABLE]